Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Contact 200

· Article number: F01888E000

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
- · Product category PC1 Adhesives, sealants
- · Process category PROC7 Industrial spraying
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

INDUSTRIE CHIMICHE FORESTALI S.p.A.

Via Kennedy 75 - 20010 Marcallo con casone (Milano) ITALY

tel. +39 02972141; fax +39 029760158

e-mail: forestali@forestali.it

- · Further information obtainable from: Environmental & Safety Department Forestali
- · 1.4 Emergency telephone number:

Tel. +39 0297214 252 Servizio Ambiente & Sicurezza Industrie Chimiche Forestali S.p.A. 8:00 - 17:00 ITALIA Centro Antiveleni Ospedale Niguarda "Ca' Granda" MILANO tel. 02/66101029; Fondazione Maugeri - Clinica del lavoro e della Riabilitazione PAVIA tel. 0382/24444; Centro Documentazione Tossicologica - Università degli Studi PADOVA tel. 049/8275078; Centro Antiveleni Istituto Scientifico "G. Gaslini" GENOVA tel. 010/5636245; Centro Antiveleni Azienda Ospedaliera "Careggi" FIRENZE tel. 055/4277328; Centro Antiveleni "Policlinico Gemelli" ROMA tel. 06/3054343; Centro Antiveleni Università degli Studi di Roma "La Sapienza" ROMA tel. 06/49970698; Centro Antiveleni Azienda Ospedaliera "A. Cardarelli" NAPOLI tel. 081/7472870; Centro antiveleni Azienda Ospedaliera Universitaria FOGGIA tel. 0881/731111

AUSTRIA Vergiftunginformationszentrale +43 1 406 43 43

BELGIUM Centre Antipoisons-Antigifcentrum +32 30245245

BULGARIA National Toxicology Centre at National Clinical Toxicology Centre +359 2 9154 233

CROTIA Poison Control Centre Zagreb +385 1 2348342

CECH REPUBLIC Toxicological Information Centre + 420224919 293

DENMARK Poison Information Centre n +45 82 12 12 12

ESTONIA Estonian Poison Information centre +372 626 93 90

FINLAND Finnish Poison Information Centre +358 9 471977

FRANCE Centre Antipoison et de Toxicovigilance de Angers +33 2 41 35 33 30

HUNGARY Health Toxicology Information Service +36 80 20 11 99

IRELAND Poison Information Centre of Ireland +353 1 809 2166

LATVIA Valsts Toksikologijas centres + 371 67042473

LITHUANIA Lithuania Poison Control and Information Bureau +370 5 236 20 52

PORTUGAL CIAV Centro de Informação Antivelenos +351 808 250 143

SLOVAKIA National Toxicological Information Center +421 2 54 774 166

POLAND Informacja toksykogiczna w Polsce +48 42 631 47 24 (czynna 7:00-15:00)

SPAIN Istituto Nacional de Toxicologia +34 156 20420

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

(Contd. on page 2)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

(Contd. of page 1)



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

602 GHS07

GHS08 GHS09

### · Signal word Danger

### · Hazard-determining components of labelling:

Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name)

Toluene

### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P240 Ground/bond container and receiving equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Additional information:

P304+P340

Contains epoxy constituents. May produce an allergic reaction.

Contains Rosin, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700), disulfiram. May produce an allergic reaction.

(Contd. on page 3)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

(Contd. of page 2)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 92062-15-2 EC number: 926-605-8 Reg.nr.: 01-2119486291-36	Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name)  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	50-70
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate  Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-15
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	Acetone  Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3, H336	5-<10
CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51	Toluene  Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	3-7%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32	Rosin  Skin Sens. 1, H317	0.5-<1
CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.1-0.7
CAS: 128-37-0 EINECS: 204-881-4 Reg.nr.: 01-2119555270-46	2,6-di-tert-butyl-p-cresol Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302	0.1-0.7
CAS: 97-77-8 EINECS: 202-607-8	disulfiram  STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Sens. 1, H317	0.1-0.7

### · UVCB (Unknown Variable Complex reaction product or Biological Origin)

None of the ingredients is listed.

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. (Contd. on page 4)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- $\cdot \textit{Information about fire and explosion protection:} \\$

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store the product in well areated local at a temperature between 5 and 35 °C. Avoid temperature up 40 °C and below 5 °C because the product could freeze and coagulate becaming unusable.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 5)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

		(Contd. of page	
· 8.1 Control parame			
	nit values that require monitoring at the workplace:		
141-78-6 Ethyl ace			
WEL Short-term vo			
67-64-1 Acetone (5	**		
,	lue: 3620 mg/m³, 1500 ppm		
	lue: 1210 mg/m³, 500 ppm		
108-88-3 Toluene (	•		
	lue: 384 mg/m³, 100 ppm lue: 191 mg/m³, 50 ppm		
Sk	uue. 191 mg/m², 30 ppm		
8050-09-7 Rosin (0	5-<1%)		
WEL Short-term vo	lue: 0.15 mg/m³		
"	lue: 0.05 mg/m³		
Sen			
· DNELs			
141-78-6 Ethyl ace			
	m-Systemic effect 63 mg/kg (workers)		
_	m-Systemic effect 1468 mg/m3 (workers)		
67-64-1 Acetone	m-Local effect   1468 mg/m3 (workers)		
	m-Systemic effect 186 mg/kg (workers)		
Inhalative Long ter			
108-88-3 Toluene	2.20		
Dermal Long ter	m-Systemic effect 384 mg/kg (workers)		
Inhalative Long ter	m-Systemic effect 192 mg/m3 (workers)		
Acute Sy	stemic effect 384 mg/m3 (workers)		
· PNECs	<u>'</u>		
141-78-6 Ethyl ace	tate		
fresh water	0.26 mg/l (frs)		
	0.26 mg/l (water)		
marine water	0.026 mg/l (mar)		
	0.026 mg/l (water)		
Intermittent release	650 mg/l (water)		
67-64-1 Acetone	lan a ga		
fresh water	10.6 mg/l (water)		
marine water	1.06 mg/l (water)		
Intermittent release sediment-marine we	21 mg/l (water) 3.04 mg/l (water)		
sediment-marine wa sediment-fresh wate	30.4 mg/l (water)		
•		100 mg/l (water)	
Soil	29.5 mg/kg (soil)		
108-88-3 Toluene	1=		
fresh water	0.68 mg/l (water)		
marine water	0.68 mg/l (water)		
sediment-marine we			

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

	(Contd. of page 5)
sediment-fresh water	16.39 mg/l (workers)
Soil	2.89 mg/kg (soil)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Opaque
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

**Boiling point/Boiling range:** 55 °C

(Contd. on page 7)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

	(Contd. of page
· Flash point:	-20 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapoumixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	110 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Soluble.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic at 20 °C:	1900 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	79.7 %
Water:	0.0 %
VOC (EU):	794.4 g/l
Solids content:	20.3 %
· 9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

	· LD/LC50 values relevant for classification:		
Γ	141-78-6 Ethyl acetate		
ſ	Oral	LD50	4935 mg/kg (rabbit)
	Inhalative	LC50/4 h	1600 mg/l (rat)

(Contd. on page 8)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

		(Contd. of page 7)	
67-64-1 A	67-64-1 Acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	20000 mg/kg (rabbit)	
108-88-3	Toluene		
Oral	LD50	5000 mg/kg (rat)	
Dermal	LD50	12124 mg/kg (rab)	
Inhalative	LC50/4 h	5320 mg/l (maus)	
128-37-0 2	,6-di-tert-l	butyl-p-cresol	
Oral	LD50	890 mg/kg (rat)	
1330-20-7	1330-20-7 xylene (mix)		
Oral	LD50	8700 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	6350 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Version number 15 Printing date 20.01.2017 Revision: 20.01.2017

Trade name: Contact 200

(Contd. of page 8)

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name ADR IMDG	1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS ADHESIVES (Solvent naphtha (petroleum), hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name), reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)), MARINE POLLUTANT ADHESIVES
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
· Class · Label	3 Flammable liquids. 3
· IATA  · Class · Label	3 Flammable liquids.
	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances 2,6-di-tert-butyl-p-cresol, Solvent naphtha (petroleum) hydrotreated light naphthenic; Hydrocarbons C6-C7 isoalkanes cyclics < 5% n-hexane (REACH Registered Name)
· Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler): · EMS Number:	- E E C D
· EMS Number: · Stowage Category	F-E,S-D A

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

	(Contd. of page
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E
·IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALL
	HAZARDOUS

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	79.4

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

Printing date 20.01.2017 Version number 15 Revision: 20.01.2017

Trade name: Contact 200

(Contd. of page 10)

· Department issuing SDS: Environmental & Safety Department Forestali

· Contact: Antonio Sassi

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* \* Data compared to the previous version altered.