

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product Name BOSTIK 6092
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

Section 2: HAZARD IDENTIFICATION

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable Liquids	Category 2 - (H225)

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

Unknown aquatic toxicity 0% of the mixture consists of components(s) of unknown hazards to the aquatic

environment

2.2. Label Elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Toluene, Methyl ethyl ketone

BOSTIK 6092 Revision Date 16-Jun-2016 Version 1

Supercedes Date: No information available



Signal Word DANGER

Hazard statements

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

H361d - Suspected of damaging the unborn child

H225 - Highly flammable liquid and vapour

EUH208 - Contains rosin. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/containers in accordance with local regulations

Special provisions concerning the labelling of certain mixtures

This product requires tactile warnings if supplied to the general public

Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment

2.3. Other Hazards

General Hazards

In use may form flammable/explosive vapour-air mixture.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture. Health hazard information is based on its components.

3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	01-2119457290-43-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	I	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	01-2119475515-33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	1	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304)	01-2119484651-34-XXXX

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

				Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066) Skin Irrit. 2 (H315)	
Ethyl acetate	205-500-4	141-78-6	10 - <20	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	01-2119475103-46-XXXX
Toluene	203-625-9	108-88-3	5 - <10	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)	01-2119471310-51-XXXX
Carbonic acid, zinc salt, basic	257-467-0	51839-25-9	1- <3	Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	01-2119474697-20-XXXX
Rosin	232-475-7	8050-09-7	0.1 - <1	Skin Sens. 1 (H317)	01-2119480418-32-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air.

Skin ContactWash with plenty of soap and water. If skin irritation occurs: Get medical advice/

attention.

Eye contact In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice. Remove contact lenses, if present and easy to do. Continue rinsing. Call a doctor

immediately.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

entry to unnecessary and unprotected personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use CO2, dry chemical, or foam.

Unsuitable Extinguishing Media

Use water spray or fog; do not use straight streams

5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

5.3. Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.

Water spray may reduce vapour; but may not prevent ignition in closed spaces.

For emergency responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Environmental precautions

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

6.3. Methods and material for containment and cleaning up

Methods for Containment Dyke far ahead of spill; use dry sand to contain the flow of material. Contain and collect

spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations

(see Section 13).

Methods for cleaning up

Use clean non-sparking tools to collect absorbed material. Dyke far ahead of liquid spill

for later disposal.

6.4. Reference to other sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION

Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ventilating/lighting /equipment.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep only in the original container/package in a cool well-ventilated place.

7.3. Specific end use(s)

Other Information

Recommendation(s); Observe technical data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Methyl ethyl ketone	TWA: 200 ppm	TWA: 200 ppm	STEL: 300 ppm

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

78-93-3	TWA: 600 mg/m³ STEL: 300 ppm STEL: 900 mg/m³	TWA: 600 mg/m³ STEL: 300 ppm STEL: 900 mg/m³ Skin	STEL: 899 mg/m³ TWA: 200 ppm TWA: 600 mg/m³ Skin
Ethyl acetate 141-78-6	-	TWA: 200 ppm STEL: 400 ppm	STEL: 400 ppm TWA: 200 ppm
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m³ STEL: 100ppm STEL: 384mg/m³ S*	TWA: 50 ppm TWA: 192 mg/m³ STEL: 384 mg/m³ STEL: 100 ppm Skin	STEL: 100 ppm STEL: 384 mg/m³ TWA: 50 ppm TWA: 191 mg/m³ Skin
Rosin 8050-09-7	-	TWA: 0.05 mg/m³ STEL: 0.15 mg/m³ Sen**	TWA: 0.05 mg/m ³
Talc 14807-96-6	-	TWA: 10 mg/m³ TWA: 0.8 mg/m³ STEL: 30 mg/m³ STEL: 2.4 mg/m³	STEL: 3 mg/m³ TWA: 1 mg/m³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield.

Skin and Body Protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic

Not applicable for liquids

or rubber. Suitable protective clothing. Apron.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical StateLiquidAppearanceLiquid

Colour White Off-white

Odour Solvent

Odour Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point/freezing point
Boiling Point 48 °C / 118.4 °F
Flash Point -9 °C / 15.8 °F
Evaporation Rate No information available

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper Flammability Limit
Lower Flammability Limit
Vapour Pressure
Vapour Density
Specific Gravity
Water Solubility

No information available
No information available
No information available
No information available
Immiscible in water

Solubility in Other Solvents

Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Explosive Properties
Explosive Limits

No information available
No information available
No information available
No information available

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

Superceues Date. No information available

Upper No information available Lower No information available Oxidising Properties No information available

Kinematic Viscosity 2500

Dynamic Viscosity No information available

9.2. Other information

Softening Point
Molecular Weight
Solvent content (%)
Solid content (%)
No information available
No information available
No information available
No information available

Density 0.86

Bulk Density No Data Available

VOC content (%)

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under recommended storage conditions.

10.2. Chemical stability

Stable under recommended storage conditions.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from heat, sparks and flames.

10.5. Incompatible materials

Strong acids and bases.

10.6. Hazardous decomposition products

Carbon oxides.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

InhalationNo Data Available.Eye contactNo Data Available.Skin ContactNo Data Available.IngestionNo Data Available.SensitisationNo Data Available.

Component Information

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

Toxicity Data No information available

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	= 2483 mg/kg (Rat) = 2737	= 5000 mg/kg (Rabbit) = 6480	= 11700 ppm (Rat) 4 h
	mg/kg (Rat)	mg/kg (Rabbit)	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rat)	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (rat)	>3350 mg/Kg (rabbit OECD 402)	259354 mg/m³ (vapour) (rat OECD 403)
Ethyl acetate	= 5620 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	LC0 29.3 mg/l air
Toluene	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 30 mg/L (Rat) 4 h
Rosin	>2800 mg/Kg (rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h

Skin Corrosion/Irritation Not applicable.

Serious eye damage/eye irritation Not applicable.

Sensitisation Not applicable.

Germ Cell Mutagenicity Not applicable.

Carcinogenicity Not applicable.

Reproductive Toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

STOT - Single Exposure No information available.

STOT - Repeated Exposure No information available.

Target Organ Effects Central nervous system, Eyes, Kidney, Liver, Respiratory system, Skin.

Aspiration Hazard No information available.

Unknown acute toxicity 0 % of the mixture consists of ingredient(s) of unknown toxicity

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methyl ethyl ketone	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50 96 h 3130 - 3320 mg/L (Pimephales promelas flow-through)	EC50 48 h > 308 mg/L (Daphnia magna)
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	-	-	EL50 (48h) =3mg/L Daphnia
Hydrocarbons, C6, isoalkanes, <5% n-hexane	13.6 mg/l (Pseudokirchneriella subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	31.9 mg/l (Daphnia magna)
Ethyl acetate	EC50 48 h = 3300 mg/L (Desmodesmus subspicatus)	LC50 96 h 220 - 250 mg/L (Pimephales promelas flow-through) LC50 96 h = 484 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h 352 - 500 mg/L (Oncorhynchus mykiss semi-static)	EC50 48 h = 560 mg/L (Daphnia magna Static)
Toluene	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata) EC50 96 h > 433 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static) LC50 96 h = 12.6 mg/L	EC50 48 h 5.46 - 9.83 mg/L (Daphnia magna Static) EC50 48 h = 11.5 mg/L (Daphnia magna)

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

		(Pimephales promelas static) LC50	
		96 h 11.0 - 15.0 mg/L (Lepomis	
		macrochirus static) LC50 96 h = 54	
		mg/L (Oryzias latipes static) LC50	
		96 h 15.22 - 19.05 mg/L	
		(Pimephales promelas	
		flow-through) LC50 96 h 50.87 -	
		70.34 mg/L (Poecilia reticulata	
		static) LC50 96 h 14.1 - 17.16	
		mg/L (Oncorhynchus mykiss static)	
		LC50 96 h = 28.2 mg/L (Poecilia	
		reticulata semi-static)	
Rosin	EC50 72 h = 400 mg/L	LC50 (96h) >10mg/L Fish (Danio	EC50 48 h >100 mg/L (Daphnia
	(Desmodesmus subspicatus)	rerio)	magna)

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other Adverse Effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other Information Waste codes should be assigned by the user based on the application for which the

product was used.

Section 14: TRANSPORTATION INFORMATION

ADR

14.1 UN/ID no UN1133

14.2 Proper Shipping Name Adhesives, Environmentally Hazardous

14.3 Hazard Class 3 Hazard Labels 3

BOSTIK 6092 Revision Date 16-Jun-2016 Version 1

Supercedes Date: No information available

14.4 Packing Group

UN1133, Adhesives, 3, III, Environmentally Hazardous Description

14.5 Environmental Hazard ves 14.6 Special Provisions 640E **Classification Code** F1 **Tunnel restriction code** D/E Limited Quantity (LQ) 5 L 30 ADR Hazard Id (Kemmler

Number)

IMDG

14.1 UN/ID no UN1133

14.2 Proper Shipping Name Adhesives (Methyl ethyl ketone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics),

Marine Pollutant

14.3 Hazard Class 14.4 Packing Group

Description UN1133, Adhesives (Methyl ethyl ketone, Hydrocarbons, C7, n-alkanes, isoalkanes,

cyclics), 3, III, (-9°C c.c.), Marine Pollutant

14.5 Marine Pollutant Not applicable 14.6 Special Provisions 223, 955 **Limited Quantity (LQ)** 5 L **EmS-No** F-E, S-D No information available

14.7 Transport in bulk according

to Annex II of MARPOL 73/78 and

the IBC Code

RID

14.1 UN/ID no UN1133

14.2 Proper Shipping Name Adhesives, Environmentally Hazardous

14.3 Hazard Class 14.4 Packing Group

Description UN1133, Adhesives, 3, III, Environmentally Hazardous

14.5 Environmental Hazard yes **Classification Code** F1 14.6 Special Provisions None Limited Quantity (LQ) 5 L

ICAO (air)

14.1 UN/ID no UN1133 14.2 Proper Shipping Name Adhesives

14.3 Hazard Class 14.4 Packing Group

UN1133, Adhesives, 3, III Description

14.5 Environmental Hazard yes 14.6 Special Provisions

IATA

14.1 UN/ID no UN1133 14.2 Proper Shipping Name Adhesives

14.3 Hazard Class Ш 14.4 Packing Group

Description UN1133, Adhesives, 3, III

14.5 Environmental Hazard yes 14.6 Special Provisions А3 Limited Quantity (LQ) 10 L 3L **ERG Code**

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

·

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No	Restrictions on use
Toluene	108-88-3	48.

48 . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H361d - Suspected of damaging the unborn child

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure if inhaled

H304 - May be fatal if swallowed and enters airways

H225 - Highly flammable liquid and vapour

H319 - Causes serious eye irritation

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

H317 - May cause an allergic skin reaction

EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation: Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

STOT (RE): Specific target organ toxicity - Repeated exposure

STOT (SE): Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By

Product Safety & Regulatory Affairs

BOSTIK 6092 Revision Date 16-Jun-2016 Supercedes Date: No information available Version 1

Revision Date 16-Jun-2016

Indication of changes

Revision Note Not applicable.

Training Advice Provide adequate information, instruction, and training for operator

Additional information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet