



Date: May 2007 Information Sheet No.: B2304-1

THERMELT 105

HOT MELT PPOLYAMIDE ADHESIVE

THERMELT 105 is a hot melt polyamide adhesive with low melt viscosity, short setting and open time and good surface wetting properties

RECOMMENDED USE

THERMELT 105 is used in the shoe industry for folding and lasting operations.

BONDING INSTRUCTIONS

- Various thermostatically controlled applicators are available to heat and melt THERMELT 105, and dispense it directly to the work piece.
- Recommended application temperature 135 to 150°C.
- Do not heat the adhesive for extended periods or when the equipment is not in use.

TYPICAL CHARACTERISTICS

Physical Form:

Colour:

Viscosity (Brookfield RVT thermosel at 150°C):

Softening Point (Ring & Ball):

Granules

Dark Amber

Approx. 3.4Pas

Approx. 106°C

PACKAGING

For current pack sizes please contact the customer service department

STORAGE

Store in original packaging in a cool dry place not exceeding 30°C, keep away from moisture.

SHELF LIFE

At least 18 months from date of manufacture under the above storage conditions.

MATERIAL SAFETY DATA

For further information refer to the relevant Health and Safety Data Sheet.

This Product Data Sheet covers just one of a large range of products supplied by Bostik Limited. Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This Product Data Sheet supersedes all previous technical information on this product, and users of it are cautioned to ensure that it is the current issue. Destroy all previous Product Data Sheets, and if any doubt, contact Bostik Limited, quoting the code number in the top right hand corner on the front of this document. This leaflet is for general guidance only and may contain inappropriate information under particular conditions of use. The company cannot accept any responsibility for loss or damage that may result from the use of this information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm the suitability of this product by their own tests.

Bostik Ulverscroft Road, Leicester, LE4 6BW England. Tel: +44 (0) 1785 272727 Fax: +44 (0) 116 253 1943