

SAFETY DATA SHEET 3939 SOLVENT

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 3939 SOLVENT

Product number C0234

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier

Caswell and Company Limited

6 Princewood Road

Earlstrees Industrial Estate Corby, Northants NN17 4AP +44 (0) 1536 464800 +44 (0) 1536 464801

info@caswell-adhesives.co.uk

caswell

1.4. Emergency telephone number

Emergency telephone In case of emergency telephone: +44 (0)1536 464800. Office hours: Mon - Thur 9am - 5pm,

Fri 9am - 2pm

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373

Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Human health The product is irritating to eyes and skin. Contains a substance/a group of substances which

may damage the unborn child. In high concentrations, vapours and spray mists are narcotic

and may cause headache, fatigue, dizziness and nausea.

Environmental The product contains a substance which is toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

Physicochemical The product is highly flammable.

2.2. Label elements

Pictogram









Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour/ spray. P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P313 Get medical advice/ attention.

Contains

TOLUENE, BUTANONE, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane,

Hydrocarbons, C6 isoalkanes < 5% n-hexane

Supplementary precautionary

statements

P202 Do not handle until all safety precautions have been read and understood.

P240 Ground/ bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TOLUENE 30-60%

CAS number: 108-88-3 FC number: 203-625-9

Classification (67/548/EEC or 1999/45/EC) Classification

Flam. Liq. 2 - H225 F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67

Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336

STOT RE 2 - H373

Asp. Tox. 1 - H304

3939 SOLVENT

BUTANONE 30-60%

CAS number: 78-93-3 EC number: 201-159-0

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-

10-30%

hexane

CAS number: — EC number: 921-024-6

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Lig. 2 - H225 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

Hydrocarbons,C6 isoalkanes <5% n-hexane

1-10%

CAS number: — EC number: 931-254-9

Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Keep affected person under observation. Get medical attention. Show this Safety

Data Sheet to the medical personnel.

Ingestion Get medical attention immediately. Do not induce vomiting.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information Treat symptomatically. The severity of the symptoms described will vary dependent on the

concentration and the length of exposure.

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion May be fatal if swallowed and enters airways.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

The product is highly flammable. Solvent vapours may form explosive mixtures with air. Specific hazards

5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Containers close to fire should be removed or cooled with water.

Special protective equipment

for firefighters

Personal precautions

Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No smoking, sparks, flames or other sources of ignition near spillage. Take precautionary measures against static discharges. Do not breathe vapour. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions

Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. Avoid eating, drinking and smoking when using the product. Good personal hygiene procedures should be implemented. Avoid inhalation of vapours and spray/mists. Provide adequate ventilation. Use approved respirator if air contamination is above an acceptable level. In use may form flammable/explosive vapour-air mixture.

3939 SOLVENT

Advice on general occupational hygiene

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep separate from food, feedstuffs, fertilisers

and other sensitive material. Store in closed original container at temperatures between 5°C

and 25°C.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³ Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³ Sk

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m³ Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m³ Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

TOLUENE (CAS: 108-88-3)

DNEL Consumer - Inhalation; Short term local effects: 226 mg/m³

Consumer - Inhalation; Short term systemic effects: 226 mg/m³ Workers - Inhalation; Short term systemic effects: 384 mg/m³ Workers - Inhalation; Short term local effects: 384 mg/m³ Workers - Inhalation; Long term local effects: 192 mg/m³ Consumer - Inhalation; Long term systemic effects: 56.5 mg/m³ Workers - Inhalation; Long term systemic effects: 192 mg/m³

PNEC - Fresh water; 0.68 mg/l

- Sediment (Freshwater); 16.39 mg/kg

STP; 13.61 mg/lSoil; 2.89 mg/kg

BUTANONE (CAS: 78-93-3)

Ingredient comments WEL = Workplace Exposure Limits

DNEL Consumer - Oral; Long term systemic effects: 31 mg/kg/day

Consumer - Dermal; Long term systemic effects: 412 mg/kg/day Workers - Dermal; Long term systemic effects: 1161 mg/kg/day Consumer - Inhalation; Long term systemic effects: 106 mg/m³ Workers - Inhalation; Long term systemic effects: 600 mg/m³

PNEC - Fresh water; 55.8 mg/l

Sediment (Freshwater); 284.7 mg/kg
Intermittent release; 55.8 mg/l
Sediment (Marinewater); 284.7 mg/l

STP; 709 mg/lSoil; 22.5 mg/kgMarine water; 55.8 mg/l

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane

DNEL Consumer - Oral; Long term systemic effects: 699 mg/kg/day

Workers - Oral; Long term systemic effects: 2035 mg/kg/day Consumer - Dermal; Long term systemic effects: 699 mg/kg/day Workers - Dermal; Long term systemic effects: 773 mg/kg/day Consumer - Inhalation; Long term systemic effects: 608 mg/m³

Hydrocarbons,C6 isoalkanes <5% n-hexane

DNEL Consumer - Oral; Long term systemic effects: 1301 mg/kg/day

Consumer - Dermal; Long term systemic effects: 1377 mg/kg/day Workers - Dermal; Long term systemic effects: 13964 mg/kg/day Consumer - Inhalation; Long term systemic effects: 1131 mg/m³ Workers - Inhalation; Long term systemic effects: 5306 mg/m³

8.2. Exposure controls

Protective equipment













Appropriate engineering F controls li

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Always check applicability with your supplier of protective equipment.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Wear tight-fitting, chemical splash goggles or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

Personal protection

protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

Environmental exposure

controls

Keep container tightly sealed when not in use. Residues and empty containers should be

taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Colourless.

Odour Aromatic.

3939 SOLVENT

Odour threshold Not determined.

pH Not applicable.

Melting point Not applicable.

Initial boiling point and range 68°C @ 760 mm Hg

Flash point -10°C CC (Closed cup).

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not determined.

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.9 Upper flammable/explosive limit: 11.5

Other flammability

Vapour pressure

22 mm Hg @ °C

Vapour density

Not determined.

Relative density 0.782 - 0.792 @ 20°C

Bulk density

Not determined.

Solubility(ies)

Insoluble in water.

Partition coefficient

Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

535°C

Explosive properties Not determined.

Comments Information declared as "Not available" or "Not applicable" is not considered to be relevant to

the implementation of the proper control measures.

9.2. Other information

Auto-ignition temperature

Refractive index Not determined.

Particle size Not determined.

Molecular weight Not determined.

Volatility 100

Saturation concentration Not determined.

Critical temperature Not determined.

Volatile organic compound This product contains a maximum VOC content of 804 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No hazardous reactions if stored and handled as prescribed.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

3939 SOLVENT

10.3. Possibility of hazardous reactions

Possibility of hazardous

Will not polymerise.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

products vapours

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅o) No specific test data are available.

Acute toxicity - dermal

Notes (dermal LD₅₀) No specific test data are available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Skin irritation., Prolonged or repeated contact with skin may cause irritation, redness and

dermatitis.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitroNo specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

Reproductive toxicity

Reproductive toxicity - fertility No specific test data are available.

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

accumulation of hazardous vapour concentrations.

3939 SOLVENT

Inhalation Vapour from this product may be hazardous by inhalation. Vapours may irritate

throat/respiratory system. Symptoms following overexposure may include the following:

Headache. Dizziness. Drowsiness.

Ingestion May be fatal if swallowed and enters airways.

Skin contact Harmful in contact with skin. Irritating to skin.

Eye contact Risk of serious damage to eyes.

Acute and chronic health

hazards

Contact with this chemical can be hazardous. May damage the unborn child. May cause

damage to organs through prolonged or repeated exposure.

Route of entry Inhalation Skin absorption Ingestion.

TOLUENE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o >5000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC50) LC50/4h >20 mg/l, Inhalation, Rat

Serious eye damage/irritation

Serious eye

damage/irritation

Irritating to eyes

Respiratory sensitisation

Respiratory sensitisation Not known.

Skin sensitisation

Skin sensitisation Not known.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity

Reproductive toxicity -

development

Suspected of damaging the unborn child

BUTANONE

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >2000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rabbit

Inhalation Vapours may irritate throat/respiratory system. Symptoms following overexposure

may include the following: Headache. Dizziness. Drowsiness. Prolonged inhalation

of high concentrations may damage respiratory system.

Ingestion May cause nausea, headache, dizziness and intoxication. Ingestion of large

amounts may cause unconsciousness.

3939 SOLVENT

Skin contact May be absorbed through the skin. Product has a defatting effect on skin. Irritating

to skin.

Eye contact Severe irritation, burning and tearing.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅o) LD₅o >2000 mg/kg, Dermal, Rabbit

Hydrocarbons,C6 isoalkanes <5% n-hexane

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ >5000 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ >2000 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC50/4h >20 mg/l, Inhalation, Rat

SECTION 12: Ecological Information

Ecotoxicity Ecotoxicological studies are not available for the product.

Do not allow to escape into waterways, wastewater or soil.

Please find below the ecotoxicological data available to us for the components.

12.1. Toxicity

Acute toxicity - fish LC₅₀, 96 hours: 6.3 mg/l, Algae

Acute toxicity - aquatic

invertebrates

Not determined.

Acute toxicity - aquatic plants Not determined.

Acute toxicity - Not determined.

microorganisms

Acute toxicity - terrestrial Not determined.

TOLUENE

Acute toxicity - fish LC₅₀, : >1 - <10 mg/l, Algae

LC₅₀, 96 hours: 13 mg/l, Carassius auratus (Goldfish)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic IC₅₀, 72 hours: 12 mg/l, Selenastrum capricornutum, Pseudokirchneriella

subcapitata

Chronic toxicity - fish early NOEC, 28 days: >1 - <10 mg/l, Algae

life stage

plants

BUTANONE

3939 SOLVENT

Acute toxicity - fish LC₅₀, 48 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane

Acute toxicity - fish LC₅₀, : 1-10 mg/l, Algae

NOEC, : 1-10 mg/l, Algae

Acute toxicity - aquatic

plants

LC₅₀, : 10-100 mg/l, Fish

Acute toxicity - LC_{50} , : 1-10 mg/l, Activated sludge microorganisms NOEC, : 0.1-1 mg/l, Activated sludge

Hydrocarbons,C6 isoalkanes <5% n-hexane

Acute toxicity - fish LC₅₀, : 10-100 mg/l, Algae

NOEC, : 1-10 mg/l, Algae

Acute toxicity - aquatic

plants

 LC_{50} , : 10-100 mg/l, Fish

Acute toxicity - NOEC, : 1-10 mg/l, Activated sludge

microorganisms

12.2. Persistence and degradability

Persistence and degradability Volatile substances are degraded in the atmosphere within a few days.

Phototransformation Not determined.

Stability (hydrolysis) Not determined.

Biodegradation Not determined.

Biological oxygen demand Not determined.

Chemical oxygen demand Not determined.

TOLUENE

Persistence and

degradability

The product is readily biodegradable.

BUTANONE

Persistence and degradability

The product is readily biodegradable.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane

Persistence and degradability

The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient Not determined.

3939 SOLVENT

BUTANONE

Bioaccumulative potential The product is not bioaccumulating.

Partition coefficient log Pow: 0.29

12.4. Mobility in soil

The product contains volatile organic compounds (VOCs) which will evaporate easily from all Mobility

surfaces.

Adsorption/desorption

coefficient

No specific test data are available.

Henry's law constant No specific test data are available.

Surface tension No specific test data are available.

BUTANONE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate

easily from all surfaces. The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

No data available

TOLUENE

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

BUTANONE

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%n-hexane

Results of PBT and vPvB This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

Hydrocarbons,C6 isoalkanes <5% n-hexane

Results of PBT and vPvB

This substance is not classified as PBT or vPvB according to current EU criteria.

assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class Hazardous waste

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993 UN No. (IMDG) 1993 UN No. (ICAO) 1993 UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name

FLAMMABLE LIQUID, N.O.S.

(ADR/RID)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S.

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class 3
ADR/RID classification code F1
ADR/RID label 3

IMDG class 3
ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II
IMDG packing group II
ADN packing group II
ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

33

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EU legislation Dangerous Preparations Directive 1999/45/EC.

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 01/08/2018

Revision 8

Supersedes date 22/06/2015 SDS status Approved.

Hazard statements in full H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.